## Waterloo Express DRG

Low velocity air diffuser for small air flows


## **Quick Facts**


- Adjustable spread pattern and affected area
- Simple installation
- Cleanable
- Available in a large number of special versions for optimum adaptation to the room



	300 x 100 (Hole Size)			
Static Pressure	Air Volume	Forward Throw @ 0.2m/s Vt (a)	Horizontal Spread @ 0.2m/s Vt (b)	Noise Level
Pa	l/s	(m)	(m)	NR
5	8	0.2	0.5	<20
10	12	0.4	0.8	<20
15	14	0.4	0.9	<20
20	17	0.5	1.1	21
25	19	0.6	1.2	24
30	21	0.6	1.4	28
35	22	0.7	1.4	29
40	24	0.7	1.6	32







## Selection Example

Air volume - 15 l/s.

Pre-selected volume (nearest table duty) - 14 l/s. Associated pre-selection pressure - 15 Pa.

Performance based on tabled volume (14), 0.4m throw @ Vt 0.2m/s, 0.9m spread @ Vt 0.2m/s, 15 Pa, <NR20

Performance adjusted to suit actual volume (15), 0.4m throw @ Vt 0.2m/s, 0.95m spread @ Vt 0.2m/s, 16 Pa, NR20

All performance is for guidance only.

Product Group	Product description	EXPRESS Part Number	Price *
Displacement	DRG/300 x 100/9005-Matt 30%	EXP-DRG-001	£32.06

<sup>\*</sup> including standard UK delivery.

