

SIGMA Zero



SIGMA Zero

High efficiency water source
chillers and heat pumps with
natural refrigerant

20÷290 kW

BlueBox 
by Swegon

SIGMA Zero

WATER

SOURCE meets natural

PROPANE

refrigerant



Single or double circuit inverter compressors unit with plate heat exchangers:

- Water cooled inverter heat pump and chiller with R290
- 4 versions for different applications
- Hot water up to 75°C
- Installation flexibility (indoor/outdoor version)
- Compact footprint
- Eurovent certified performance

MISSION
ZERO
EMISSION

CLIMATE CHANGE FIGHT



EUROPEAN CLIMATE STRATEGY IS GOING TO BE UPDATED AND REINFORCED

TARGET

Reduction of **55%** Greenhouse Gas emission by **2030**

Increased **renewable energy** (above **32%**) by **2030**

Net-zero Greenhouse Gas Emission by **2050**



HOW?

F-gas regulation Regulation

Renewable Energy Directive

European Performance of Buildings Directive (**EPBD**)

Ecodesign **ERP** Directive

Keep temperature increase below **1.5°C**

Become a climate neutral economy

R290

NATURAL REFRIGERANT



SUSTAINABLE CHOICE


- Nearly zero Global Warming Potential (GWP≈0*)
- Natural non toxic refrigerant
- No Ozone Layer impact
- 40% gas charge compare to R410A

RELIABLE CHOICE

- Implementation of the highest safety standard

SMART CHOICE

- No carbon tax
- Pushed by incentivisation schemes
- Future-proof natural solution. On going HFC phase-out



(*) GWP (AR6), pursuant to IPCC VI, evaluated over a span of 100 years.

TEWI

TOTAL EQUIVALENT WARMING IMPACT

TEWI [tons CO₂ eq.]

Direct emissions + Indirect emissions


Leakage rate per year
Service life (years)

Leftover refrigerant after disposal
Global Warming Potential

Plant cooling / Heating load
Efficiency

Electricity consumption
CO₂ emission intensity


European electricity carbon intensity is dropping, so **natural** heat pumps become day by day more **sustainable** and will contribute to Europe **decarbonization** and **climate neutrality**



Electricity emission intensity [gCO₂e/kWh], 2019 data, Source EEA

SIGMA Zero HAS
MINIMUM CARBON FOOTPRINT
THANKS TO ITS
HIGH EFFICIENCY
AND
LOW CHARGE OF PROPANE

CAPACITY RANGE/VERSIONS



Cooling and Heating capacity according EN14511

OPERATING LIMITS



Space heating and domestic hot water production **up to 75°C**

Comfort cooling and process applications **-15°C ÷ 20°C**



INDOOR INSTALLATION
Ventilated enclosure class IV*

INSTALLATION FLEXIBILITY

OUTDOOR INSTALLATION
Open space class III*

*UNI EN 378

SAFE INDOOR INSTALLATIONS
Automatic Air-Refrigerant Separator

BOOSTERLINK



System
Integration

- Optimal synergy between the Swegon units
- 3-way valve control of the SIGMA Zero source temperature
- A single-point of control and monitoring

SIGMA Zero Hi OH

BOOSTERLINK



Swegon Heat Pump



BLUEYE CONNECT

REMOTE ACCESS TO UNIT

SAVE MONEY
FAST SERVICE

BLUEYE CLOUD

CLOUD RECORDING DATAPOINTS

PREDICTIVE MAINTENANCE
CUSTOMER REPORTING
ANALYSIS



SIMULTANEOUS MANAGEMENT

PLANT
management



Multilogic
indoor
installation

Option available
common safety circuit fan serving
multiple machines (up to 5)

HYZER HYDRONIC OPTIMIZER

BLUETHINK solution to manage several units,
components and devices and build an
optimized System.

- **Advanced algorithms** to maximize system total efficiency
- **Less Opex** thanks to lower energy consumption
- **Flexible management** of multi units, variable water flow and external devices (drycoolers, cooling towers, boilers,...)
- **Real time** energy consumption to obtain advanced structured data analysis
- **Modular design** to perfectly suit any project requirements in terms of application, size and complexity



Feel good **inside**

