

CALMO, CADENZA, LARGO, LENTO, MORENDO

Installation – Maintenance

2025-05-05



CALMO



CADENZA



LARGO



LENTO



MORENDO

General

Check the mechanical functions of the product before and after you install it. A damaged or faulty product should not be installed. Report faults immediately to your nearest Swegon representative.

Dimensions and Weights

The dimensions can be read on the product rating label and are specified as width x height x length.

The sound attenuator weighs approx. 100 kg/m.³ (N.B.!) This is a rough estimate. For exact weights, contact your nearest Swegon sales representative.)

Commissioning

The sound attenuator does not need to be commissioned.

For particulars of how to check the pressure drop across the sound attenuator, refer to the product datasheet of the sound attenuator on the Internet.

Inspection

The product rating label is affixed to opposite sides of the sound attenuator.

Installation

Correct installation is a prerequisite for the sound attenuator to operate in an optimum way. Otherwise its technical performance, such as pressure drop, integral attenuation and natural sound generation, may be substantially impaired.

“Correct installation” implies that the sound attenuator should be installed in a run of straight ducting having a length equivalent to 4 x D (D is the largest side of the sound attenuator) upstream and downstream of the sound attenuator.

If the sound attenuator is placed near duct bends or other aerodynamically inappropriate duct components, its pressure drop and natural sound generation will probably be greater than the values of these specified in the catalogue. The connection of a plenum to the inlet or outlet of the sound attenuator also substantially increases the pressure drop.

IMPORTANT! The attenuator inlet side is where the baffles are rounded, mount attenuator in the correct direction of airflow according to product labeling!

When suspending the sound attenuator, angle brackets must be fitted to support its entire width; accordingly the sound attenuator must not be mounted solely suspended from its points of connection.

Maintenance

The sound-attenuating material, ISOVER Cleantec® PLUS, is a type-approved insulation material consisting of long-fibred compressed mineral wool, protected by special perforated aluminium foil. ISOVER Cleantec® PLUS is type-approved with regard to cleaning, fibre entrainment, resistance to ageing and emissions, etc., to type-approval number 2706/92.

For the type approval to be valid, dry methods for cleaning the insulation material must be employed, such as the use of a rotating nylon brush (it is NOT permissible to use a steel brush), vacuum cleaning or wiping off surfaces with a dry cloth.

The slab can also be cleaned using a wet method. Manual washing with a sponge or cloth.

The sheet metal surfaces can be cleaned with water and detergent.

Tears and holes in the ISOVER Cleantec® PLUS can be repaired with aluminium tape.